



**Albi Manufacturing**

Division of StanChem, Inc  
401 Berlin Street  
East Berlin, CT 06023  
Emergency Telephone Number: CHEMTREC 1-800-424-9300  
Information Telephone Number: 860-828-0571  
Date of Preparation: 3/3/2015

**Section I – Product Identification**

**Product Number:** 15x0100 series  
**Product Name:** Albi 107A  
**Product Class:** Fire Retardant Coating

**Section II –Hazard Identification**

**Hazard Classification:** Flammable Liquid Class 1B

**Symbol:**



**Signal Word:** Danger

**Hazard Statements:** Highly Flammable Liquid and Vapor. Harmful if inhaled.  
May cause respiratory irritation. May cause drowsiness or dizziness.  
Harmful to aquatic life

**Precautionary Statements:**

Keep container tightly closed. Use only non sparking tools.  
Keep away from heat and flames.  
No Smoking. Containers must be properly grounded before beginning transfer.  
Do not breathe vapors. Do not contact eyes, skin and clothing.  
Wear protective gloves. Wash hands thoroughly after using  
Dispose of in accordance with local, regional, national, international regulations as specified

**Section III-Hazardous Ingredients**

Ingredient	CAS#	Weight%	Occupational Exposure Limits	
			ACGIH TLV (ppm)	OSHA PEL (ppm)
Solvent Naptha, Heavy aromatic	64742-94-5	5.0-6.0	NE	NE
t-Butyl Acetate	540-88-5	10.0-11.0	200	200
Napthalene	91-20-3	0.4-0.6	10	10
Aromatic Petroleum Distillates	64742-95-6	2.0-2.5	NE	NE
Aliphatic Hydrocarbons (Stoddard)	8052-41-3	1.0-1.5	100	100
1,2,4 Trimethyl Benzene	95-63-6	0.4-0.6	25	25
1,3,5 Trimethyl Benzene	108-67-8	0.1-0.2	25	25

Xylene\*

1330-20-7

12.0-13.0

100

100

\*Contains Ethylbenzene

CAS#101-44-4

---

#### Section IV – First Aid Measures

---

##### First Aid Procedures:

**Inhalation:** Remove individual to fresh air. Administer oxygen if breathing is difficult. Consult a physician

**Skin:** Wash thoroughly with soap and water. Remove contaminated clothing

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Consult a physician.

**Ingestion:** Dilute with clear fluid, then immediately call a Physician or the Poison Control Center.

---

#### Section V – Fire and Explosion Hazard Data

---

##### Flammability Classification:

OSHA	Flammable Liquid – Class 1B
DOT	Flammable Liquid, PGII
Flash Point	65° F TCC – Tag Closed Cup
LEL	1.7% at 212° F

**Extinguishing Media:** Foam Alcohol Foam CO<sub>2</sub> Dry Chemical

##### Unusual Fire and Explosion Hazards:

Keep container tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition source causing a flashback fire. Use water to keep exposed containers cool. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

---

#### Section VI – Accidental Release Measures

---

##### Steps to be Taken in Case Material is Released or Spilled:

Avoid all sources of ignition. Ventilate area. Stop spill at source, dike to prevent spreading. Pump liquid into containers. The remainder should be removed with inert absorbent use non-sparking tools.

---

#### Section VII – Safe Handling and Storage

---

**Handling:** Use only non sparking tools. Keep away from heat and flames. Containers must be properly grounded before beginning transfer. Empty containers may contain product residue; follow MSDS and label warnings even after the container has been emptied.

**Storage:** Store closed drums with bung up position. Store only in tightly closed properly vented containers. Avoid exposing product to heat above 150°F. Store below 90°F

---

#### Section VIII – Exposure Controls and Personal Protection

---

**Respiratory Protection:** Approved chemical/mechanical filters designed to remove a combination of organic vapors during application.

**Ventilation:** Local exhaust as required by job conditions to keep TLV below acceptable limits. Refer to OSHA regulations 29 CFR Part 1910.94.

**Protective Gloves:** Wear chemical resistant gloves

**Eye Protection:** Use safety eyewear with splash guards or side shields

**Other Protective Equipment:** None.

**Hygienic Practices:** Eye wash and shower should be available. Use under well ventilated conditions. Personnel should wash thoroughly after handling product. Always wash-up before eating, smoking or using the toilet facilities. Do not breathe vapor, do not contact eyes, skin and clothing.

---

**Section IX – Physical Data**

---

Boiling Point	208°- 335°F (82° - 177°C)
Weight per Gallon	10.2-11.2 lb./gal
Percent Volatility	32.0 – 34.0 %
Viscosity	85-110 KU
Solids	66-68%
VOC content:	341 g/L

---

**Section X – Stability and Reactivity**

---

**Stability:** Stable

**Hazardous Polymerization:** Will Not Occur

**Hazardous Decomposition Products:** Combustion may produce carbon dioxide and/or carbon monoxide.

**Conditions To Avoid:** Heat, sparks, open flame, other ignition sources, and oxidizing conditions

**Incompatibility [Materials to avoid]:** Strong oxidizing agents

---

**Section XI – Toxicological Information**

---

**Primary Routes of Exposure**

Eye Contact  
Skin Contact  
Inhalation  
Ingestion

**Medical Conditions Prone to Aggravation by Exposure:** Sinus Dermatitis

**Product Toxicology**

<b>Carcinogenicity:</b>	NTP?	No
	IARC Monographs?	Ethyl Benzene – Group 2B
	OSHA Regulated?	No

---

**Section XII – Ecological Information**

---

**Potential to Bioaccumulate:** Unknown

**Aquatic Toxicity:** No data available for this product

---

**Section XIII – Disposal Considerations**

---

**Waste Disposal Methods:**

Disposal should be in accordance with local, state and federal regulations.

**Empty Container Warnings:**

Empty containers may contain product residue; follow MSDS and label warnings even after the container has been emptied.

**Section XIV – Transportation**

<b><u>Proper Shipping Name:</u></b>	15X0100 series
<b><u>Technical Name:</u></b>	Paint
<b><u>Identification Number:</u></b>	UN1263
<b><u>Hazard Class/Division:</u></b>	3 (Flammable Liquid)
<b><u>Packing Group:</u></b>	II

**Section XV – Regulatory**

**TSCA**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

**SARA 313 Reporting**

A number of the constituents within the formulation are required to be reported under this regulation.

**California Prop 65**

<b>Cancer List:</b>	Napthalene, Benzene
<b>Reproductive Harm</b>	Benzene, Toluene

**Section XVI – Other Information**

**Hazard Rating Systems**

<b>NFPA 704*</b>		<b>HMIS**</b>		<b>Key:</b>	<b>0 - Insignificant;</b>
<b>Health:</b>	<b>2</b>	<b>Health:</b>	<b>2</b>	<b>1=Slight</b>	<b>2 = Moderate;</b>
<b>Flammability</b>	<b>3</b>	<b>Flammability</b>	<b>3</b>	<b>3=High</b>	<b>4= Extreme;</b>
<b>Reactivity</b>	<b>0</b>	<b>Reactivity</b>	<b>0</b>	<b>I= Respirator, Eye Protection and gloves</b>	
		<b>Personal Protection</b>	<b>I</b>		

\*National Fire Protection Association rating identifies the severity of hazards of material during a fire emergency (i.e., “on fire”)

\*\*Hazardous Materials Identification System, National Paint and Coatings Association rating applies to product “as packaged” (i.e., ambient temperature)

**NOTICE**

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of StanChem's knowledge or obtained from sources believed by StanChem to be accurate. StanChem does not assume any legal responsibility for use or reliance upon same information. Customers are encouraged to conduct their own tests. For additional technical information contact StanChem.