



**Albi Manufacturing**

Division of StanChem, Inc

401 Berlin Street

East Berlin, CT 06023

Emergency Telephone Number: CHEMTREC 1-800-424-9300

Information Telephone Number: 860-828-0571

Date of Preparation: 3/2/2015

**Section I – Product Identification**

**Product Number:** 16x0018  
**Product Name:** Albi Clad 800 Trowel Grade  
**Product Class:** Intumescent Mastic

**Section II –Hazard Identification**

**Hazard Classification:** Flammable Liquid Class 1C

**Symbol:**



**Signal Word:** Danger

**Hazard Statement:** Flammable Liquid and Vapor

**Precautionary Statements:**

Keep container tightly closed. Use only non sparking tools.

Keep away from heat and flames.

No Smoking. Containers must be properly grounded before beginning transfer.

Do not breathe vapors. Do not contact eyes, skin and clothing.

Wear protective gloves. Wash hands thoroughly after using

Dispose of in accordance with local, regional, national, international regulations as specified

**Section III-Hazardous Ingredients**

NE – Not Established

N/A – Not Applicable

Ingredient	Percent Wt.	Occupational Exposure Limits					Vapor Pressure @20°C (mmHg)
		ACGIH TLV (ppm)	OSHA TWA (ppm)	OSHA STEL (ppm)	Ceiling (ppm)	Skin	
t-Butyl Acetate CAS #[540-88-5]	24.9	200	200	200	NE	NE	34
1-methoxy-2-acetoxy Propane CAS # [108-65-6]	1.4	NE	NE	NE			3.7
Solvent Naphtha (petroleum) Medium Aliphatic CAS # [64742-88-7]	0.8	100	100	NE			2.9
Ethylene Glycol Monobutyl Ether CAS #[111-76-2]	1.1	NE	20	NE			0.4

Xylene* CAS # [1330-20-7]	0.4	100	100	150	6.0
Aromatic Petroleum Distillates CAS #[64742-95-6]	2.0	NE	NE	NE	N/A
Isopropyl Alcohol CAS #[67-63-0] * - Contains ethylbenzene CAS # [100-41-4]	1.3	400	400	NE	2.1

---

#### Section IV – First Aid Measures

---

**First Aid Procedures:**

<b>Inhalation:</b>	Remove individual to fresh air. Administer oxygen if breathing is difficult. Consult a physician
<b>Skin:</b>	Wash thoroughly with soap and water. Remove contaminated clothing
<b>Eyes:</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Consult a physician.
<b>Ingestion:</b>	Dilute with clear fluid, then immediately call a Physician or the Poison Control Center.

---

#### Section V – Fire and Explosion Hazard Data

---

**Flammability Classification:**

OSHA	Flammable Liquid – Class 1C
DOT	Flammable Liquid, PGII
Flash Point	72° F TCC – Tag Closed Cup
LEL	1.7% at 212° F

**Extinguishing Media:**Foam Alcohol Foam CO<sub>2</sub> Dry Chemical Fog**Unusual Fire and Explosion Hazards:**

Keep container tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition source causing a flashback fire. Use water to keep exposed containers cool. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

---

#### Section VI – Accidental Release Measures

---

**Steps to be Taken in Case Material is Released or Spilled**

Avoid all sources of ignition. Ventilate area. Stop spill at source, dike to prevent spreading. Pump liquid into containers. The remainder should be removed with inert absorbent use non-sparking tools.

---

#### Section VII – Safe Handling and Storage

---

**Handling:**

Use only non sparking tools. Keep away from heat and flames. Containers must be properly grounded before beginning transfer. Empty containers may contain product residue; follow MSDS and label warnings even after the container has been emptied.

**Storage:**

Store closed drums with bung up position. Store only in tightly closed properly vented containers.

---

 Section VIII – Exposure Controls and Personal Protection
 

---

<b><u>Respiratory Protection:</u></b>	Approved chemical/mechanical filters designed to remove a combination of organic vapors and solid airborne particles from overspray during application.
<b><u>Ventilation:</u></b>	Local exhaust as required by job conditions to keep TLV below acceptable limits. Refer to OSHA regulations 29 CFR Part 1910.94.
<b><u>Protective Gloves:</u></b>	Wear chemical resistant gloves
<b><u>Eye Protection:</u></b>	Use safety eyewear with splash guards or side shields
<b><u>Other Protective Equipment:</u></b>	None.
<b><u>Hygienic Practices:</u></b>	Eye wash and shower should be available. Use under well ventilated conditions. Personnel should wash thoroughly after handling product. Always wash-up before eating, smoking or using the toilet facilities. Do not breathe vapor, do not contact eyes, skin and clothing.
<b><u>Precautions To Be Taken in Handling and Storing:</u></b>	Keep away from heat or open flames
<b><u>Other Precautions:</u></b>	Avoid contact with eyes and skin

---

 Section IX – Physical Data
 

---

Boiling Point	180° - 350°F (82° - 177°C)
Weight per Gallon	10.3-10.7 lb./gal
Percent Volatility	33.0 – 35.0 %
Viscosity	350,000-400,000 cps
Solids	65-67%
VOC content:	248 g/L

---

 Section X – Stability and Reactivity
 

---

<b><u>Stability:</u></b>	Stable
<b><u>Hazardous Polymerization:</u></b>	Will Not Occur
<b><u>Hazardous Decomposition Products:</u></b>	Combustion may produce carbon dioxide and/or carbon monoxide.
<b><u>Conditions To Avoid:</u></b>	Heat, sparks, open flame, other ignition sources, and oxidizing conditions
<b><u>Incompatibility [Materials to avoid]:</u></b>	Strong oxidizing agents

---

 Section XI – Toxicological Information
 

---

**Primary Routes of Exposure**

Eye Contact  
 Skin Contact  
 Inhalation  
 Ingestion

Medical Conditions Sinus Dermatitis  
Prone to Aggravation  
by Exposure:

Product Toxicology  
Carcinogenicity: NTP? No  
 IARC Monographs? Ethyl Benzene – Group 2B  
 OSHA Regulated? No

Section XII – Ecological Information

Potential to Bioaccumulate: Unknown  
Aquatic Toxicity: No data available for this product

Section XIII – Disposal Considerations

Waste Disposal Methods:  
 Disposal should be in accordance with local, state and national regulations.

Section XIV – Transportation

Technical Name: Albi Clad 800  
Proper Shipping Name: Paint  
Identification Number: 3  
Hazard Class/Division: UN1263  
Packing Group: PGII  
Harmonized System Code 320890

The information provided herein may not include the impact of additional regulatory requirements (e.g. for materials meeting the definition of a hazardous waste under RCRA, hazardous substances under CERCLA, and/or marine pollutants under CWA or other similar federal, state or local laws) or any associated exceptions or exemptions under regulations applicable to the transport of this material.

Section XV – Regulatory Information

TSCA and DSL  
 All components of this product are on the DSL and TSCA Inventory or are exempt from DSL and TSCA Inventory requirements.

SARA 313 Reporting  
 A number of the constituents within the formulation are required to be reported under this regulation.

Section XVI – Other Information

Hazard Rating Systems

<u>NFPA 704*</u>		<u>HMIS**</u>		<u>Key:</u>	0 - Insignificant;
Health:	2	Health:	2	1=Slight	2 = Moderate;
Flammability	3	Flammability	3	3=High	4= Extreme;
Reactivity	1	Reactivity	1	I= Respirator, Eye Protection and gloves	
		Personal Protection	I		

\*National Fire Protection Association rating identifies the severity of hazards of material during a fire emergency (i.e., "on fire")

\*\*Hazardous Materials Identification System, National Paint and Coatings Association rating applies to product "as packaged" (i.e., ambient temperature)

---

**NOTICE**

**This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of StanChem's knowledge or obtained from sources believed by StanChem to be accurate. StanChem does not assume any legal responsibility for use or reliance upon same information. Customers are encouraged to conduct their own tests. For additional technical information contact StanChem.**