

BMQX.R2810 - COATINGS, FIRE RETARDANT

Coatings, Fire Retardant

See General Information for Coatings, Fire Retardant

ALBI MFG, DIV OF STANCHEM INC
 401 BERLIN ST
 EAST BERLIN, CT 06023-1127 USA

R2810

Fire retardant coatings designated as "**Albi Cote FRL**" and "**Albi Cote FRL-X**". No preliminary coats or overcoats.

**Fire Retardant /
 Coating Surface**

**"Albi Cote FRL"
 or "Albi Cote FRL-X" /
 Red Oak**

Flame spread	10
Smoke developed	50-75
Number of preliminary coats	None
Rate per coat (Sq ft per gal)	—
Number of fire-retardant coats	1
Rate per coat (Sq ft per gal)	150
Number of overcoats	None
Rate per coat (Sq ft per gal)	—

Flash point of liquid coating:

Fire-retardant coating: Albi Cote FRL & Albi Cote FRL-X: Closed cup, No flash.

Last Updated on 2019-04-25

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"