



- Thin-film, intumescent fire protective paint for wood, sheet rock, and other interior substrates
- Attractive water-based architectural finish rated for up to two hours fire protection
- Complies with all building codes for use in new construction, historic restoration, defective construction, and many other applications.





Environment

Interior products have a significant impact on indoor air quality, and can emit hundreds of chemicals into the air that building occupants breathe. GREENGUARD Certification helps provide assurance that products are low-emitting, and contribute to healthier interiors.

Representative samples of products that have achieved GREENGUARD Certification have been tested and certified to meet some of the world's most rigorous, thirdparty chemical emissions standards—helping reduce indoor air pollution and the risk of chemical exposure while aiding in the creation of healthier indoor environments. GREENGUARD Certification has been widely adopted as a trusted standard for low-emitting products. In fact, more than 400 green building codes, standards, guidelines, procurements policies, and rating systems recognize or reference GREENGUARD Certified products. To confirm continuous low emissions performance, GREENGUARD Certified products are required to undergo regular compliance testing on critical components.

Certification Types

GREENGUARD Certification is an internationally recognized product emissions certification and labeling program for manufacturers of low-emitting indoor products, furnishings, and materials. Products can be certified under two different standards:

- GREENGUARD Certification is the first voluntary North American productemissions certification created specifically for commercial building products. This certification verifies that products meet stringent chemical emission limits originally developed as purchasing specifications for building projects for the US Environmental Protection Agency and the State of Washington. GREENGUARD Certified products are compliant with stringent emission levels for over 360 VOCs, plus a limit on the total of all chemical emissions combined (TVOC).
- GREENGUARD Gold Certification includes safety factors to account for sensitive individuals (such as children and the elderly) and helps ensure that a product is acceptable for use in environments such as schools and healthcare facilities. In addition to limiting emissions of over 360 VOCs and total chemical emissions, GREENGUARD Gold Certified products must also comply with requirements of the State of California's Department of Public Health "Standard Method for the Testing and Evaluation of Volatile Organic Chemical Emissions from Indoor Sources Using Environmental Chambers, Version 1.2, 2017 (also known as California Section 01350).

The Competitive Advantage

GREENGUARD Certification provides a competitive advantage in an increasingly "green washed" marketplace by serving as a health-based differentiator. Once products are certified, manufacturers can label products with the GREENGUARD Certification mark and list them the GREENGUARD Sustainable Product Guide, a purchasing tool used by thousands of architects, interior designers, building managers and other specifying professionals. The free, online product guide is available at www.greenguard.org.

Why Choose UL Environment?

Built on UL's century-long legacy of trust, UL Environment empowers both manufacturers and purchasers to transform their environmental stewardship into true market leadership. We enable manufacturers to create better products in a more environmentally-responsible way, and enable customers to make smarter, more environmentally-preferable purchasing decisions.

How to Get Started

For more information on UL Environment's services and how they can benefit your company, visit www.ul.com/environment.

View the GREENGUARD Product Guide for certified products, including:

- Furniture
- Mattresses
- Textiles
- Flooring
- Ceiling Systems
- Building Materials
- Paints, Coatings and Adhesives
- Wallcoverings
- Cleaning and Maintenance Products
- Electronic Products



To learn more, visit ul.com/environment or call 1.888.485.4733

ALBI CLAD FP

Albi Clad FP is an interior, water-based, thin film intumescent fireproofing, tested for one hour fire resistance on wood, drywall and concrete. This hard, durable, abrasion resistant product has a smooth, aesthetic finish. Albi Clad FP is ideal for application in occupied areas or other locations where solvent-base fireproofing materials cannot be used. Because of its water-base formulation Albi Clad FP is fully compliant with EPA VOC limits and regulations.

Albi Clad FP is classified by UL, and meets all the accelerated environmental tests for interior intumescent fireproofing (general purpose space). Additionally, Albi Clad FP meets all requirements for UL follow-up service.

Wood and drywall rating up to 2 hours.

UL Design N607: For use in US and Canada. Details fire rating of 1-3 hours for floor beams.

RECOMMENDED USES

Albi Clad FP is recommended for interior use in areas such as:

- Industrial Plants
- Correctional Facilities
- Atriums
- Power Generating Facilities
- Hospitals
- Warehouses
- Parking Garages
- School Gymnasiums
- Food Processing Plants
- Computer Chip Manufacturing
- Convention Centers
- Sports Stadiums
- Historic Renovations

PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	VALUE
Hardness	Shore D	65
Compressive Strength	ASTM D695	300 psi
Cohesive/Adhesion Strength	ASTM D4541	190 psi
Abrasion Resistance	ASTM D4060	.3 grams loss
Impact Resistance	ASTM D2794	85 in/lbs.
Weight per Gallon		11.5 ± 0.20 lbs./gals
% Solids by weight		72% ± 2.0%
Flame Spread	ASTM E84	2 - Class A
Smoke Developed	ASTM E84	5 - Class A
VOC		15.6 g/L

HISTORIC RENOVATIONS, RESTORATIONS OR PRESERVATION

Albi Clad FP is ideal for renovating historical buildings. Not only does its attractive finish help maintain and retain the historic character of older buildings that make available tax credits, it provides uncompromising fire safety as well.



FEATURES:

- Factory formulated, single component
- UL tested to ASTM E-119 Standard
- UL tested for interior general purpose
- Water-based
- Thin film application
- 100% Asbestos Free
- Lightweight & hammer-hard
- Will not dust, flake or delaminate





For all Albi Clad FP information, go to www.albi.com
For no cost material estimates, please contact Albi.

Also inquire about these fireproofing products from Albi:

Albi Clad TF+

Water-based intumescent fireproofing for interior structural steel. TF+ is UL classified for 1-4 hours of protection, leaving a smooth architectural finish.

Albi Clad 800

Intumescent fireproofing, withstands severe weathering and abuse

Albi DriClad

Low-cost, uniform density mineral board that installs dry year-round

Albi Cote TB

The first coating to pass NFPA 286 over foam. A single application, water-based, one-part, non-flammable intumescent coating for interior use

Albi Cote IB

Non-flammable water-based intumescent coating that complies with AC 377 ICCES for interior use



ALBI PROTECTIVE COATINGS

For 75 years, Albi fireproofing materials have demonstrated superior performance and reliability under a range of extreme environments worldwide. These proprietary formulations also meet global building codes and insurance requirements. Lightweight Albi materials provide long-term protection, outstanding durability, aesthetic properties and are completely free from asbestos.

Albi Protective Coatings, Division of StanChem, Inc.

401 Berlin Street, East Berlin, Connecticut 06023 U.S.A.

Tel: (860) 828-0571

www.albi.com

info@albi.com



Made in the USA

