

## Interior Alkyd Enamel, Product #400-429

**Description:** An exceptional lead & chromate free low VOC interior/exterior alkyd paint for use on interior/exterior surfaces. For new or previously painted surfaces. Used on wood, metal concrete. For doors, trim, dados, railings, machinery, metal partitions, and factory equipment.

**Color(s):** All colors available

**Finish:** High Gloss

**Vehicle type:** Alkyd

**Solvent type:** N/A

**VOC:** 2.82 Lbs/Gallon, 340 Grams/Liter

**Flash point:** 105° F. Set Flash

**Solids by volume:** 57.28%

**Weight per gallon:** 9.77 Lbs

**Coverage:** Theoretical coverage at 1 mil dry is 916 square feet per gallon, and 458 square feet at 2 mils dry.

**Viscosity:** 80-90 KU (Kreb Units)

**Surface preparation:** Remove all grease, dirt, oil, wax and other foreign matter from surfaces. Bare wood and other rough surfaces should be sanded smooth. Glossy areas should be dulled by sanding.

**Shelf life:** 12 Months

**Mixing:** Stir thoroughly and apply as it comes from the container.

**Recommended dry film:** 2 Mil

**Recommended dry time:** Dries to touch in 4 Hours. Can be recoated in 8-12 hours.

**Recommended primers:** N/A

**Safety information:** Do not take internally. Close container after each use. Keep from freezing. KEEP OUT OF REACH OF CHILDREN.

**Dux Paint LLC.**

18 Mill Street, Lodi NJ 07644

Office - (973)-473-2376, Fax - (973)-473-1648