

Clear Epoxy Sealer, Product #EPS-501

Description: A two component, 1:1 ratio polyamide cured clear epoxy sealer for excellent adhesion to concrete. Provides an excellent base for the application of chemical resistant coatings such as epoxies and polyurethanes.

Color(s): Clear

Finish: Gloss

Vehicle type: Epoxy polyamide

Solvent type: Glycol Ether, Aromatic hydrocarbons, Ketone

VOC: N/A

Flash point: 50° F. (mixed)

Solids by volume: 42.3%

Weight per gallon: 7.9 Lbs (mixed)

Coverage: Theoretical coverage at 1 mil dry is 678 square feet per gallon, and 339 square feet at 2 mils dry.

Viscosity: 35-40 seconds (#4 Ford cup)

Surface preparation: Remove all grease, dirt, oil, wax and other foreign matter from surfaces. Clean, Dry, contaminant free.

Shelf life: 12 Months

Mixing: Mix Ratio: 1:1 By Volume. Stir thoroughly each component, combine in proper ratio. Give ½ hour induction period before using. Mix only what will be used in an 8 hour period.

Recommended dry film: 2 Mil

Recommended dry time: Set to touch in 1 Hour. Recoat within 12 hours.

Recommended primers: N/A

Safety information: FLAMMABLE! HARMFUL OR FATAL IF SWALLOWED, FLAMMABLE LIQUID AND VAPOR, SKIN AND EYE IRRITANT. CONTAINS GLYCOL ETHER, KETONES. Vapor harmful, may affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Keep away from heat, sparks and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave area. Do not take internally. Close container after each use. Avoid contact with skin or eyes.

Dux Paint LLC.

18 Mill Street, Lodi NJ 07644

Office - (973)-473-2376, Fax - (973)-473-1648