

FISH EYE ELIMINATOR

PRODUCT:	Fish Eye Eliminator
DESCRIPTION:	Fish eye eliminator helps prevent cratering and fish eyes in the lacquer surface..
SUGGESTED USES:	Designed to prevent fish eyeing in lacquer surfaces.
TESTING:	After adding fish eye eliminator the complete system should be tested for appearance prior to full scale application.
ADVANTAGES:	Ease of use, Quick results supplied in a dropper bottle for easy additions.
DIRECTIONS:	Mix in 10 drops per gallon, test sample, if condition is not eliminated add by drop until condition is eliminated. Excess fish eye eliminator will make condition worse.
SOLIDS BY VOLUME:	57.28%
WEIGHT PER GALLON:	9.77 Lbs
SHELF LIFE:	36 Months minimum.
SAFETY INFORMATION:	FLAMMABLE! HARMFULL OR FATAL IF SWALLOWED, CONTAINS LACQUER THINNER.. Keep away from heat, sparks and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave area. Do not take internally. Close container after each use. Avoid contact with skin or eyes.
FISRT AID:	If swallowed, do not induce vomiting. Call a physician immediately. In case of eye contact, immediately flush thoroughly with water and call a physician. For skin contact, wash thoroughly. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks and flame.

All technical data, recommendations and services are accurate to the best of our knowledge. Seller assumes no responsibility for the results obtained or damages incurred from their use by the Buyer in whole or in part. No Warranty, including those of merchantability or fitness for a particular purpose, is expressed or implied since the method of application and its use is beyond our control. There are no warranties that extend beyond the description or the face hereof.

DUX PAINT LLC.

OFFICE ADDRESS: 18 mill STREET, LODI NJ 07644
(973)473-2376 FAX# (973)473-1648