## PRE-CATALYZED LACQUER

**PRODUCT NAME:** Interior Varnish **PRODUCT NUMBERS:** PC-15, PC-20 **DESCRIPTION:** An exceptional high solids Pre-catalyzed nitrocellulose lacquer product. Its properties include, fast drying, self sealing with excellent resistance to water, solvent and household chemicals Designed for interior wood surfaces on kitchen and bathroom and **SUGGESTED USES:** all parts of furniture. **TESTING:** Due to the wide valiety of substrates, surface preparation methods, and environments, the complete system should be tested for adhesion and compatibility under their conditions prior to full scale application. **COLORS:** Clear - Also Available in Colors FINISH: PC15 (15° sheen) PC-20 (20° sheen). PC Gloss Other sheens available on request. **FLASH POINT:** 60° F. Seta Flash **SOLIDS BY VOLUME:** 52.6% **WEIGHT PER GALLON:** 7.84 Lbs **COVERAGE:** Theoretical coverage at 1 mil dry is 841 square feet per gallon, Not including spray loss VISCOSITY: 25-36 @77°F./25° C. Ford #4 **RECOMMENDED DRY TIME:** Dries to touch in 15 to 20 minutes. Sanding 30 minutes **REDUCER:** Ready For use, No reducer needed. **CLEAN UP:** Lacquer Thinner SURFACE PREPERATION: Remove all grease, dirt, oil, wax and other foreign matter from surfaces. Bare wood and other rough surfaces should be sanded smooth. Glossy areas should be dulled by sanding. MIXING: Mix well before use



36 Months minimum.

SHELF LIFE:

OFFICE ADDRESS: 18 mill STREET, LODI NJ 07644 (973)473-2376 FAX# (973)473-1648

**APPLICATION:** Brush, Roller Spray.

Roll:  $\frac{1}{4}$ " –  $\frac{1}{2}$ " synthetic roller cover or  $\frac{1}{2}$ " Lambswool.

Conventional Air Spray:	Binks	Graco	Devilbiss
Spray Gun:	#18	800	JGA502
	Or #62	or 900	or MBC-510
Fluid Nozzle:	66 or 67	047 or 086	D or E
Air Cap:	66PE or 63PB	02,03, 952	704,765,78
Airless Spray:	Binks	Graco	
Pump:	98-999 Super bee 23:1 Monarch		
Pressure Filter:		100 Mesh	
Fluid Hose:	71-7505	¼ " x 50'	
Airless Gun	#1M	208-663	
Tips:	9-1860	.013017	
Minimum Pressure:		1800 PSI	

HVLP: Binks

Spray Gun: Mach 1
Fluid Nozzle: 94F or 905F
Orifice .070 or .086
Air Nozzle: 95AP or 905P

**MIXING:** Stir thoroughly and apply as it comes from the container.

SAFETY INFORMATION: FLAMMABLE! HARMFULL OR FATAL IF SWALLOWED, CONTAINS LACQUER THINNER.. Keep away from heat,

sparks and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave area. Do not take internally. Close container after each use. Avoid contact with skin or eyes.

If swallowed, do not induce vomiting. Call a physician immediately. In case of eye contact, immediately flush thoroughly with water and call a physician. For skin contact, wash thoroughly.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **Keep away from heat, sparks** and flame.

.....

FISRT AID: