

Optimal Handling and Storage Guidelines for Intumescent Coatings

The performance and longevity of intumescent coatings are highly dependent on proper handling and storage methods. Mishandling or unsuitable storage conditions, notably exposure to excessive cold or heat, can have detrimental effects on the product's physical attributes and its useful life, potentially making it unusable. Always refer to and comprehend the Safety Data Sheets (SDS) and Technical Data Sheets (TDS) provided by Albi Protective Coatings for manufacturer's guidelines.

● COATING FEATURES:

- Eco-friendly and safe
- Aqueous formulation
- pH levels between 7-8
- Boiling threshold at 212°F (100°C)
- Freezing limit at 32°F (0°C)
- Mild or virtually no scent

● SAFE HANDLING AND STORAGE CONDITIONS:

- Maintain a temperature range of 40°F (4°C) to 90°F (32°C)
- Use only the original packaging, stored in a cool, dry place
- Always keep the container upright
- Avoid direct exposure to sunlight

● SUPPLEMENTARY SAFETY PRECAUTIONS:

- The prevailing weather conditions may dictate the suitable settings for both applying and securely storing the intumescent coating on-site. If temperatures fall below 40°F (4°C) or exceed 90°F (32°C), consider taking extra measures for product handling and storage. It is vital to adhere to the outlined **SAFE HANDLING AND STORAGE CONDITIONS** during transportation of the product.

